

DrillAir E35

Oil lubricated air compressor - electrical driven



General information

Dimensions (L x W x H)	mm	4972 x 2234 x 2215	Min ambient temperature	°C	-25
Weight max/full	kg	7500	Max ambient temperature	°C	+45 @ 17 barg
	lbs	18298	Air outlet temperature	°C	a+22
Sound Pressure Level acc ISO2151	dB(A) @7m	101	Air outlet connection		G2"Mantex
Electrical connections		Powerlock x 2			

Motor

Voltage	V	400	Max power consumption	kW	500
Frequency	Hz	50-60	Max line current	A	890

Performance

Min discharge pressure	barg	15			psig	216
Max discharge pressure	barg	32			psig	464
Max free air delivery	m³/min	35,4			cfm	1250

Set pressure		Max free air delivery @ set pressure		Max required power at set pressure	Max line current at set pressure
barg	psig	m³/min	cfm	kW	A
17	246	35.4	1250	410	740
25	363	34.2	1208	448	809
32	464	33	1165	488	882

Main features

Variable speed drive	Low noise operation
CE certified	Up to 35% energy savings
Low starting current	



Atlas Copco Rental

www.atlascopcorental.com

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.